



A versatile bench top robot that can be converted to **dispensing, dotting, gasketing, spraying** platform easily

<b>3-axis bench top programmable dispensing robot</b>				
<b>Models:</b>	<b>E720-3</b>	<b>E730-3</b>	<b>E740-3</b>	<b>E750-3</b>
Working Range X * Y * Z (mm) :	200 * 200 * 50	300 * 300 * 100	400 * 400 * 100	500 * 500 * 150
Load Y-AXIS / Z-AXIS (kg):	5 / 3	10 / 5	10 / 5	10 / 5
Speed X&Y / Z (mm/sec) :	0.1-500 / 250	0.1-800 / 500		
Resolution :	0.01 mm/Axis			
Repetitive Positioning Accuracy :	+/- 0.01 mm/ Axis			
Program Capacity :	Min 100 Group、 4000 points/group			
Data Storage Type :	CF Card			
Program Display :	Teach Pendant LCD			
Motor System :	3 Phase Micro-stepping motor			
Control Method :	PTP & CP			
Interpolation Function :	3 axis (suit for 3D requirement)			
Programming Method :	Teach pendant / Keyboard			
I/O Signals Port :	8 Inputs / 8 Outputs			
External Control Interface :	RS232			
Power Supply :	AC 110 ~ 220V 300W			
Working Temperature :	10 - 40 °C			
Working Relative Humidity :	20 - 90% no condensation			
Dimensions W*D*H (mm) :	385 * 380 * 500	485 * 505 * 610	585 * 610 * 610	685 * 700 * 660
Net Weight (kg) :	23	32	41	52



**ABLE INDUSTRIAL ENGINEERING** Email: [sales@aie.sg](mailto:sales@aie.sg)  
 50 Chin Swee Road, #09-04 Thong Chai Building, Singapore 169874